

KINETIC TOW ROPE

When brute force isn't enough, control makes the difference.

In demanding recovery situations, sudden shocks can damage equipment and increase risk. Southern Ropes Kinetic Tow Ropes are designed to change that; converting momentum into a smooth, controlled pulling force that works with the terrain, not against it. The result is a safer, more reliable recovery, even in deep sand, mud, or challenging off-road conditions.

FEATURES

- Engineered for dynamic recovery
- Elastic recovery action
- Shock absorption
- Hard-wearing construction
- Soft handling
- Spliced eyes
- ISO 1140

TECHNICAL

- Material: Nylon
- Construction: 12-Strand (6x2)
- Standard range: 20-80mm Diameter
- Length: Made to order
- Terminations: Spliced Eyes
- Colour: White



Gross Vehicle Weight (t)	Diameter (mm)	Break Load (Kg)
2.00 & under	20	8 300
2.50 - 5.00	24	12 000
5.00 - 7.99	36	24 800
8.00 - 11.99	40	30 000
12.00 - 15.41	48	42 000
15.50 - 18.49	52	48 800
18.50 - 21.99	58	58 000
22.00 - 23.99	60	63 800
24.00 - 30.99	64	72 000
31.00 - 43.99	68	78 500
44.00 - 54.99	72	90 000
55.00 - 65.00	80	110 000

Always select a rope with an adequate safety factor for the application.

Safety First

- Use only anchoring points connected directly to the chassis and rated by the manufacturer.
- Use correctly sized rated connectors / shackles.
- Never use a kinetic rope on a winch or as a winch cable extension.
- Never tie knots in the rope.
- Never use a damaged rope.
- Never combine or extend the rope with other ropes, webbings, chains, or cables.
- Keep bystanders clear of the recovery zone.
- Keep rope clean and free from sand or grit.

