

SuperBraid

Super-12® with a high-tenacity polyester cover.

This high-performance rope is designed for sailing applications where ultra-low stretch is required. The high UV rating of the core means that the cover can be stripped without fear of a UV-related loss in strength.

FEATURES

- Lightweight
- Ultra-low stretch
- UV Resistant Core
- Polyester sheath prevents block and jammer slippage

TECHNICAL

- Core: Super-12® UHMwPE
- Cover: HT Polyester
- Construction: Double Braid
- Colour: Colour & White Mottle

OPTIONS

- Protective Cover Braids
- Spliced Eyes
- Thimbles
- Proof Loading Certificate

DIAMETER

- 4-30 mm (larger diameters available on request)

LENGTHS

- 200 m reels
- Custom lengths available

APPLICATIONS

- Wire Rope Replacement
- Winch Lines
- Hoist Lines
- Towing
- Halyards
- Check Stays
- Strops
- Cargo Nets
- General Purpose
- Towing Rope for Water Sport
- Rescue Line
- Nets



Diameter (Inches)	Diameter (mm)	Spliced Break Load (Metric Tonne)	Linear Break Load (Metric Tonne)
3/16"	4	0.28	0.31
3/16"	5	0.85	0.94
1/4"	6	1.30	1.40
1/4"	7	2.20	2.40
5/16"	8	3.10	3.40
3/8"	9	4.30	4.70
3/8"	10	5.20	5.70
1/2"	12	8.30	9.20
9/16"	14	10.90	12.00
5/8"	16	15.30	16.90
3/4"	18	17.90	19.80
13/16"	20	27.00	29.90
7/8"	22	31.30	34.70
1"	24	40.80	45.20
1-1/16"	26	47.00	52.10
1-1/8"	28	55.20	61.20
1-1/4"	30	65.30	72.40

We offer an extensive range of larger diameters and longer lengths - available up to 168mm. Get in touch with us today to find the perfect fit for your needs.